



800 Martha Street – Pittsburgh, PA 15120
412/462-6300

#364 Polyester Adhesive Tape

#364 Polyester Adhesive Tape offers a very thin product with high conformability, high tear resistance and good dielectrics. Typical applications include barrier insulation in bobbin coils and end turn bundling on small fractional and sub-fractional horsepower motors. This tape can also be used for formed coil construction for holing start and end points of mica tape.

This tape is made with a thermoset acrylic adhesive. It gives the tape excellent chemical resistance. This adhesive also holds up well when exposed to intermittent temperatures of 155°C.

Properties	Value*
Color	Clear and Yellow
2.2mil (.06mm)	2.2mil (.055mm)
Standard Length	72 yards (66meters)
Insulation Class	B (130)
Peel Strength	28 oz/in (3N/cm)
Tensile Strength	19 lb/in (33N/cm)
Elongation	80%
Breakdown Voltage	5kv
Resistivity	4x10 ³

Product supply:

1. Color and thickness can be produced upon request.
2. Shelf Life: One year from the date of delivery.
It can still be used if it is qualified by testing after one year according to above Technical Requirement.

Note:

1. Above values are only typical values and should not be used in writing specifications.
2. The color is only confirmed by samples.

***CAUTION:** The above values are typical and care should be taken not to take this data as a basis in constructing any specifications. All customers are responsible to ensure that this product will meet all application requirements before approving this for use.